

PAGE TWO - N-209 PRO-KLEEN HEAVY DUTY FLOOR CLEANER

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:	INHALATION? YES	SKIN? YES	INGESTION? YES
--------------------	--------------------	--------------	-------------------

HEALTH HAZARDS (ACUTE AND CHRONIC): INHALATION: MAY CAUSE DAMAGE TO THE UPPER RESPIRATORY TRACT. SKIN: CAN PRODUCE SEVERE BURNS AND DESTROYS TISSUES. EYES: CAN CAUSE SEVERE BURNS THAT RESULT IN DAMAGE TO THE EYES AND POSSIBLY BLINDNESS. INGESTION: CAN CAUSE SEVERE BURNS TO MUCOUS MEMBRANES OF THE MOUTH, THROAT, AND STOMACH. NO KNOWN CHRONIC EFFECTS.

CARCINOGENICITY: NTP? NO	IARC MONOGRAPHS? NO	OSHA REGULATED? NO
--------------------------	---------------------	--------------------

SIGNS AND SYMPTOMS OF EXPOSURE: INHALATION: MAY CAUSE COUGHING, SNEEZING, OR OTHER SYMPTOMS. EYES: PAIN, REDNESS. SKIN: ITCHING OR BURNING. INGESTION: BURNING OF THROAT, MOUTH, AND STOMACH.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE KNOWN

EMERGENCY AND FIRST AID PROCEDURE: INHALATION: REMOVE VICTIM TO FRESH AIR. EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: FLUSH THOROUGHLY WITH COOL WATER. INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: LEAKS SHOULD BE STOPPED IMMEDIATELY. SPILLS SHOULD BE CONTAINED AND CLEANED UP. LIQUID SPILLS SHOULD BE REMOVED BY USING A VACUUM TRUCK.

WASTE DISPOSAL METHOD: DISPOSE OF ACCORDING TO FEDERAL, STATE, AND LOCAL HEALTH ENVIRONMENTAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP CONTAINERS CLOSED WHEN NOT IN USE. PROTECT EYES AND SKIN FROM CONTACT.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN PROTECTION IS REQUIRED FOR CERTAIN OPERATIONS, USE AN APPROVED AIR-PURIFYING RESPIRATOR.

VENTILATION: USE LOCAL EXHAUST WHERE SPRAY/MIST MAY BE GENERATED.

PROTECTIVE GLOVES: RUBBER GLOVES ARE RECOMMENDED.

EYE PROTECTION: CHEMICAL GOGGLES ARE RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: IMPERVIOUS PROTECTIVE CLOTHING ARE RECOMMENDED.

WORK/HYGIENIC PRACTICES: WASH THOROUGHLY AFTER HANDLING. DO NOT GET INTO EYES, ON SKIN, ON CLOTHING. DO NOT TAKE INTERNALLY.

**** END OF M.S.D.S. ****

MATERIAL SAFETY DATA SHEET

STATE PROCUREMENT
DATE PREPARED:
02 AUG 2002
REVISED: JUNE 1, 2002

IDENTITY (AS USED ON LABEL AND LIST): N-209 PRO-KLEEN HEAVY DUTY
FLOOR CLEANER
#7930-017-001

SECTION I

MANUFACTURER'S NAME: NAR ENTERPRISES, INC.
EMERGENCY TELEPHONE NUMBER: (253)476-9401 OR 1-888-474-5699

ADDRESS: 5202 SOUTH PROCTOR STREET, BLDG. A
TACOMA, WASHINGTON 98409-2713

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS CHEMICAL NAME:	OSHA PEL	ACGIH TLV	OTHER LIMITS	PERCENT
ETHYLENE GLYCOL MONOBUTYL ETHER (CAS #111-76-2)	25 PPM (SKIN)	25 PPM (SKIN)	NONE	5%
SODIUM METASILICATE (CAS #6834-92-0)	2MG/M3 (CEILING)	2MG/M3 (CEILING)	NONE	6%
SODIUM HYDROXIDE (CAS #1310-73-2)	2MG/M3 (CEILING)	2MG/M3 (CEILING)	NONE	5%

NO OTHER INGREDIENTS CONSIDERED HAZARDOUS.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: APPROXIMATELY 212F. SPECIFIC GRAVITY: APPROXIMATELY 1.02
VAPOR PRESSURE (MM HG): NOT APPLICABLE MELTING POINT: NOT APPLICABLE
pH CONCENTRATE: APPROXIMATELY 13.2
VAPOR DENSITY (AIR=1): N/A EVAPORATION RATE(BUTYL ACETATE=1): SLOWER
SOLUBILITY IN WATER: COMPLETELY SOLUBLE
APPEARANCE AND ODOR: CLEAR YELLOW LIQUID WITH SLIGHT ODOR.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NON-FLAMMABLE FLAMMABLE LIMITS: N/A LEL: N/A UEL: N/A
EXTINGUISHING MEDIA: THIS PRODUCT IS NOT COMBUSTIBLE. FOAM, CARBON DIOXIDE
OR DRY CHEMICAL.
SPECIAL FIRE FIGHTING PROCEDURES: WEAR FULL PROTECTIVE CLOTHING IF NECESSARY.
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

SECTION V - REACTIVITY DATA

STABILITY: STABLE HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID INSTABILITY: NONE
MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: NONE KNOWN
HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN